

MF 260 Specifications

PERFORMANCE

Engine power at 2,250 rpm	60 (B.S.) hp*
Torque at 1,600 Engine rpm	212 Nm
PTO power at rated engine speed	48 hp**

* Certified to BS AU 141a: (1971)

** Manufacturer's estimate

ENGINE

Type	Diesel
No. of cylinders	3
Injection	Direct
Bore	91.5 mm
Stroke	127 mm
Capacity (litres)	2.5
Aspiration	Turbo
Compression ratio	15.5:1
Starting aid	Thermostart
Throttle control	Hand and foot
Cooling	Water
Air Cleaner Type	Oil bath
Air Pre-Cleaner	Over bonnet
Fuel filter	Dual, high capacity
Exhaust	Vertical
Oil Cooler	Air Cooled, Fin Type

ELECTRICS

Voltage	12V, Negative Earth
Battery	118 Ah
Starter motor	2.2 kW
Alternator	32 Amp.

CLUTCH

Type	Dual
Diameter	305x254 mm

TRANSMISSION

Type	Sliding spur
Number of gears	8 forward, 2 reverse
Road speed at 2,250 engine rpm with 14.9/13-28 rear tyres	
Gear	Speed (km/hr)
Forward 1 (first low)	2.6
Forward 2	3.8
Forward 3	5.2
Forward 4	7.0
Forward 5 (first high)	10.4
Forward 6	15.2
Forward 7	20.8
Forward 8	27.9
Reverse 1 (low)	3.5
Reverse 2 (high)	14.1

POWER TAKE OFF

Type	Live
Engine speed at 540 PTO rpm	1,789 rpm
Shaft diameter	35 mm
No. of splines	6

HYDRAULICS

Functions	Draft control, Position control, Response Control, Constant pumping
Pump Type	Reciprocating Ferguson Pump
Oil Flow	16 l/min
Pressure	21 MPa at normal operating temperature
Lift capacity with lower links horizontal	2,145 kg
Lower Links	With Cat. I & II interchangeable balls

FRONT AXLE

Type	Box Section, Adjustable
Steering	Manual

REAR AXLE AND BRAKES

Axle Type	Straddle with epicyclic reduction unit
Brake Type	Oil immersed, multi-disc
Brakes Actuation	Mechanical
Parking Brake	Hand Lever Operated

INSTRUMENTATION

Gauges	Tachometer, Hourmeter, Fuel level, Battery condition & Water temperature
Warning lights	Direction indicators, Electric charge, Headlight main beam, Low engine oil pressure, Brake lights & Auxiliary socket

TYRES

Front	7.50-16 (6PR)
Rear	14.9/13-28 (6 PR)

TRACK ADJUSTMENT

Front	1,245-1,854 mm
Rear	1,423-2,134 mm

WEIGHT AND DIMENSIONS (Approx.)

(With 7.50-16 front and 14.9/13-28 rear wheel and with full fuel, oil and water)

Weight	
Gross Weight	1,900 kg
Dimensions	
Wheel base	1,892 mm
Overall length	3,260 mm
Overall width (min.)	1,890 mm
Height	
Over Exhaust	2,220 mm
Over Steering Wheel	1,490 mm
Turning circle	
With brakes	5,840 mm
Without brakes	6,580 mm
Ground clearance	
Under gear box	400 mm

CAPACITIES

Fuel Tank	47.5 l
Engine sump	6.8 l
Cooling system	10.2 l
Hydraulic system	36.0 l
Steering box	0.9 l
Oil bath air cleaner	0.5 l

STANDARD EQUIPMENT

Weight frame without weights, Standard tool box with set of tools, Top link, Top link end Cat I & II balls, Check chains, Spring suspension seat, Flat top fenders & Operator's & Service Manual.

OPTIONAL EQUIPMENT

Front end weights, Swinging drawbar, Sun Canopy, Pintle hook and 9 Hole drawbar.

Note:

Millat Tractors Ltd. reserve the right to change specifications without prior notice.